ORACLE®



ORACLE®


Using Automatic Workload Repository for Database Tuning: Tips for Expert DBAs

Kurt Engeleiter Product Manager The following is intended to outline our general product direction. It is intended for information purposes only, and may not be incorporated into any contract. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described for Oracle's products remains at the sole discretion of Oracle.

Oracle Enterprise Manager

Top-Down, Integrated Application Management

- Complete, Open, Integrated Management for Oracle Technologies
 - Deep, Optimized, Best of Breed
 - Database, Middleware, Packaged Applications,
 Physical and Virtual Infrastructure
- Business Centric, Top Down Application Management
- Complete Lifecycle Management
- Scalable Grid and Cloud Management
 - Manage many as one






- Automatic Workload Repository Infrastructure
- Out of the box AWR reports
- Active Reports



Automatic Workload Repository (AWR)



Fundamental Concepts

DB Time

- Total time in database calls by foreground sessions
- Includes CPU time, IO time and non-idle wait time
- DB Time <> response time
- Total DB time = sum of DB time for all active sessions

➤ Goal: To Reduce Total DB time

- Active Session
 - Session currently spending time in a database call, i.e., accruing DB time
- Average Active Sessions $=\frac{DB \text{ Time}}{Wall-Clock (Elapsed) \text{ Time}}$
- Average Active Sessions is a key metric for measuring DB load

Multiple Sessions


Total DB Time = Sum of DB Time Over All Sessions

Avg. Active Sessions = Sum of Avg. Activity Over All Sessions

= Total Database Time


Wall-Clock (Elapsed) Time

At time t we have 2 active sessions




AWR Data

- Time Model
 - v\$sys_time_model => dba_hist_sys_time_model
 - DB Time
 - Automatic Tracking of Operation Times
 - Overall parse time (hard, soft, failed,..)
 - SQL, PLSQL and Java overall execution times
- Wait Model
 - v\$system_event => dba_hist_system_event
 - Wait Events Categorized Based On Solution Area
 - More than 900 different wait events. 12 wait classes (Application, Concurrency..)
- SQL statement statistics
 - v\$sqlstats => dba_hist_sqlstat
 - Resource Usage: Executions, Physical Reads, Physical Writes
 - Efficient Top SQL identification using deltas in the kernel
- OS Stats
 - v\$osstat => dba_hist_osstat
 - CPU + Memory




AWR Data

- Snapshots
 - DBA_HIST_SNAPSHOT
 - Tracks Snapshots in the AWR
 - When querying AWR, always join to other tables to constrain the time frame



AWR Data






Active Session History (ASH)


- ASH is session level data
- Active sessions are sampled and persisted in-memory
 - Sampling interval = 1 second
 - V\$ACTIVE_SESSION_HISTORY
 - Foreground and background sessions are sampled
- On-disk persistence
 - DBA_HIST_ACTIVE_SESS_HISTORY
- ASH is a system-wide trace of what happened
- ASH is a many-dimensional FACT table
 - Dimensions are V\$SESSION columns
 - Fact is that DB time was accumulating over these dimensions

Active Session History (ASH)




Time	SID	Module	SQL ID	State	Event
7:38:26	213	Book by author	qa324jffritcf	WAITING	db file sequential read
7:42:35	213	Get review id	aferv5desfzs5	CPU	
7:50:59	213	Add to cart	hk32pekfcbdfr	WAITING	buffer busy wait
7:52:33	213	One click	abngldf95f4de	WAITING	log file sync

ASH




Circular buffer in SGA

AWR and ASH in Enterprise Manager





Top Activity



SQL Details

Details





General

Module perl@tdsmng04-d1 (TNS V1-V3)
Action

Parsing Schema CUST01
PL/SQL Source (Line Not
Number) Applicable
SQL Profile n/a
SQL Plan Baseline n/a


Shared Cursors Statistics

Total Parses 764
Hard Parses 49
Child Cursors 1
Loaded Plans 1
Invalidations 0
Largest Cursor Size (KB) 12.64
All Cursor Size (KB) 12.64
First Load Time Sep 1

First Load Time Sep 11, 2009 6:22:16 PM (UTC-05:00)

Last Load Time Sep 13, 2009 3:35:18 PM (UTC-05:00)

Activity By Waits



Execution Statistics

		Per	Per
	Total	Execution	Row
Executions	764	1	1.00
Elapsed Time (sec)	2,134.48	2.79	2.79
CPU Time (sec)	0.85	<0.01	<0.01
Buffer Gets	9,398	12.30	12.30
Disk Reads	0	0.00	0.00
Direct Writes	0	0.00	0.00
Rows	764	1.00	1
Fetches	0	0.00	0.00

Activity By Time

Elapsed Time (sec) **2,134.48** CPU Time (sec) **0.85** Wait Time (sec) **2,133.63**

Elapsed Time Breakdown


SQL Time (sec) 2,134.48 PL/SQL Time (sec) 0.00 Java Time (sec) 0.00

Other Statistics

Executions that Fetched all Rows (%) 100.00
Average Persistent Mem (KB) 4.57
Average Runtime Mem (KB) 4.02
Serializable Aborts 0
Remote No
Obsolete No
Child Latch Number 0

Agenda

- Automatic Workload Repository Infrastructure
- Out of the box AWR reports
- Active Reports



AWR Reporting Resources

- Enterprise Manager is the preferred way to view and analyze AWR and ASH data
- In addition, predefined AWR html reports are provided in each Oracle database release
- Each report has a specific function and use case
- The following slides show the major reports and their use cases



AWR Reporting Resources

- Available in
 - Enterprise Manager
 - \$ORACLE_HOME/rdbms/admin

REPORT NAME	SQL Script
Automatic Workload Repository Report	awrrpt.sql
Automatic Database Diagnostics Monitor Report	addmrpt.sql
ASH Report	ashrpt.sql
AWR Diff Periods Report	awrddrpt.sql
AWR Single SQL Statement Report	awrsqrpt.sql
AWR Global Report	awrgrpt.sql
AWR Global Diff Report	awrgdrpt.sql





How do I read an AWR report?

AWR Report

- The AWR report is the most well known performance report.
- Oracle tuning professionals frequently start their analysis with this report.
- AWR report contains much data – but contains no concrete recommendations for action.

WORKLOAD REPOSITORY report for

DB Name	DB Id	Instance	Inst nu	m	Sta	tup Time	:	Release	RAC	
PROD	48067057	prod	rd 1 27			g-09 18:0	8	11.1.0.7.0	NO	
Host Name	e Pla	atform	CPUs	C	ores	Socket	s	Memory	(GB)	
tdsmng03-d1	3-d1 Linux IA (32-l		4		2		2		5.82	
	\(\frac{1}{2}\)									
	Snap I	d Sn	ap Time		Se	essions	•	Cursors/Ses	sion	
Begin Snap:	263	24 29-Aug	g-09 20:20	0:41		38			3.2	
End Snap:	263	25 29-Aug	29-Aug-09 20:30:43			36			2.7	
Elapsed:		10.	10.04 (mins)							
DB Time:		29.	99 (mins))						

Load Profile


₩\$	Per Second	Per Transaction	Per Exec	Per Call
DB Time(s):	3.0	8.7	0.03	0.02
DB CPU(s):	2.4	6.9	0.02	0.01
Redo size:	5,201.5	15,206.5		
Logical reads:	127,103.4	371,583.6		
Block changes:	22.1	64.6		
Physical reads:	1,032.8	3,019.3		
Physical writes:	1.8	5.3		
User calls:	184.6	539.6		
Parses:	72.7	212.5		
Hard parses:	51.5	150.6		
W/A MB processed:	879,631.8	2,571,582.1		
Logons:	0.1	0.2		
Executes:	115.4	337.2		
Rollbacks:	0.2	0.5		
Transactions:	0.3			

Tip: Check ADDM Report When Viewing AWR Report

- When viewing AWR report, always check corresponding ADDM report for actionable recommendations
- ADDM is a self diagnostic engine designed from the experience of Oracle's best tuning experts
- Analyzes AWR data automatically after an AWR snapshot
- Makes specific performance recommendations
- Consistent never has a 'bad' day
- ADDM also tells you what is NOT a problem

ADDM Report

- ADDM lists the tuning opportunities with the highest benefit.
- ADDM makes specific, actionable recommendations.
- ADDM also lists areas of the system that are performing well – that don't need tuning.



Summary of Findings

	Description	Active Sessions Percent of Activity	Recommendations
1	CPU Usage	2.11 75.33	3
2	Top SQL by DB Time	1.47 52.57	3
3	Hard Parse Due to Literal Usage	.95 34.06	1
4	Row Lock Waits	.45 16	1


Miscellaneous Information

Wait class "Commit" was not consuming significant database time.
Wait class "Concurrency" was not consuming significant database time.
Wait class "Configuration" was not consuming significant database time.
Wait class "Network" was not consuming significant database time.
Wait class "User I/O" was not consuming significant database time.
Session connect and disconnect calls were not consuming significant database time.



ADDM Impact Breakdown

 In Oracle Database 11g Release 2, ADDM can break down the impact of it's findings by several dimensions including service, and session.





AWR Global Report - RAC

- RAC AWR Report
- Report rewritten and renamed in Oracle Database 11.2. spawrrac.sql => awrgrpt.sql
- All statistics from AWR placed in comparative format, along with sums, averages and standard deviations, making it easy to compare performance of RAC nodes.

WORKLOAD REPOSITORY REPORT (RAC)

Database Instances Included In Report

• Listed in order of instance number, I#

1#	Instance	Host	Startup	Begin Snap Time	End Snap Time	Release	Elapsed Time(min)	DB time(min)	Up Time(hrs)
•	bug1ap	dbs232	18-Jul-09 01:44	20-Jul-09 07:00	20-Jul-09 10:30	11.2.0.1.0	210.17	1,630.72	56.77
2	2 bug2ap	dbs233	18-Jul-09 01:45	20-Jul-09 07:00	20-Jul-09 10:30	11.2.0.1.0	210.12	1,403.79	56.75

Time Model Statistics

- Time Model
- Time Model % of DB time

Back to Top

Time Model

14	DB time (s))B CPU (s)	SQL Exec Ela (s)	Parse Ela (s)	Hard Parse Ela (s)	PL/SQL Ela (s)	Java Ela (s)	bg time (s)	bg CPU (s)
1	97,843.05	22,933.50	85,066.94	4,744.21	3,785.93	3,596.60	0.00	19,832.38	9,272.84
2	84,227.29	22,788.27	73,345.78	3,393.95	2,549.83	3,382.22	0.00	19,364.87	9,140.41
Sum	182,070.34	45,721.77	158,412.72	8,138.17	6,335.76	6,978.82	0.00	39,197.24	18,413.25
Avg	91,035.17	21,860.89	79,206.36	4,069.08	3,167.88	3,489.41	0.00	19,598.62	9,206.62
Std	9,627.80	102.69	8,288.11	954.78	874.05	151.59	0.00	330.58	93.64

My database was running fine yesterday but it is really slow today? What has changed?

Tip: Use AWR Compare Periods Report to Identify Changes in Database Performance

- AWR Compare Periods Report
 - awrddrpt.sql single instance
 - awrgdrpt.sql RAC
- Compares database performance over two time periods
- Good for identifying what changed in performance
- Tip: Save AWR snapshots of time periods with good performance for reference
- Example:
 - Overall system performance resulting from database upgrade



AWR Global Compare Periods Report

- Compares global RAC performance for two time ranges
- This report compares the performance of a two node RAC system, before and after an upgrade from Oracle Database 11.1.0.7 to Oracle Database 11.2.

WORKLOAD REPOSITORY RAC Compare Period Report for

Set	DB Id	Inst #	Instance	Release	Host	Startup	Begin Snap Time	End Snap Time	Elapsed Time (min)	DB time (min)	Instance Up Time (hrs)	Avg Active Sessions	Platform
1st	1679034986	1	b1rac	11.1.0.7.0			13-Jul-09 07:00	13-Jul-09 10:30	210.07	1,929.71	229.24		Linux IA (32-bit)
		2	b2rac	11.1.0.7.0			13-Jul-09 07:00	13-Jul-09 10:30	210.07	1,298.80	229.23		Linux IA (32-bit)
2nd	1679034986	1	b1rac	11.2.0.1.0			20-Jul-09 07:00	20-Jul-09 10:30	210.17	1,630.72	56.77		Linux IA (32-bit)
		2	b2rac	11.2.0.1.0		18-Jul-09 01:45	20-Jul-09 07:00	20-Jul-09 10:30	210.12	1,403.79	56.75	6.68	Linux IA (32-bit)


AWR Global Compare Periods Report (cont.)

 The Load Profile shows a reduction in DB Time per second and per transaction after the upgrade – overall performance has improved. The upgrade was a success.

Load Profile

	1st per sec	2nd per sec	%Diff	1st per txn	2nd per txn	%Diff
DB time:	15.37	14(44	-6.05	1.52	1(43	-5.92
CPU time:	3.06	3.14	2.01	0.30	0.31	9.93
Redo size:	412,176.31	486,745.64	18.09	40,845.08	48,084.27	17.72
Logical reads:	51,390.61	47,690.30	-7.20	5,092.61	4,711.19	-7,49
Block changes:	4,089.18	3,448.61	-15.66	405.22	340.68	-15.93
Physical reads:	4,996.38	5,295.81	5.99	495.12	523.16	5.66
Physical writes:	59.45	52.65	-11.44	5.89	5.20	-11.71
User calls:	894.08	1,051.95	17.66	88.60	103.92	17.29
Parses:	369.98	397.41	7.41	36.66	39.26	7.09
Hard parses:	15.87	19.55	23.19	1.57	1.93	22.93
W/A MB processed:	2,716,342.99	2,558,789.85	-5.80	269,179.10	252,775.84	-5.80
Logons:	9.34	9.19	-1.61	0.93	0.91	-2.15
Executes:	1,269.08	1,521.87	19.92	125.76	150.34	19.55
Transactions:	10.09	10.12	0.30			

Comparative Performance Analysiswith AWR Baselines



- AWR Baseline contains a set of AWR snapshots for an "interesting or reference" period of time
- Baseline are key for performance tuning to
 - guide set alert thresholds
 - monitor performance
 - compare advisor reports
- User-specifiable, schedulable, e.g.:
 - last Thanksgiving period
 - every Monday 10am-noon for 4 Mondays
- Automatically captures 8-day moving window baseline for week to week comparisons (default)

A user complains that his session seemed to hang for a few minutes. What happened?

Tip: Use ASH for Targeted Performance Diagnostics

- AWR snapshots and reports cover entire system
- Transient events can be averaged over a snapshot and be nonobvious from an AWR report
- ASH can be used for examining:
 - Targeted time range
 - A specific
 - session
 - service
 - wait_class
 - client_id
 - SQL_ID
 - A targeted time range in combination with the above

ASH Report

- Click on 'Run ASH Report' button from performance page
- Select time range and dimension to report on



ASH Report:

- ASH Report of a single session for a 5 minute period
- The session accounted for 52% of database activity for the time period
- The session spent 64%
 of the time in a
 concurrency wait event,
 36% on CPU. There is
 clearly some opportunity
 for tuning.

ASH Report For PROD/prod

(1 Report Target Specified)

DB Name DB	iu ilistalic	e Inst num	Release	KAC	Host
PROD \(\sigma^{\sqrt{4806}}\)	7057 prod	1	11.1.0.7.0	NO	tdsmng04-d1

CPUs	SGA Size	Buffer Cache	Shared Pool	ASH Buffer Size
4	798M (100%)	128M (16.0%)	248M (31.1%)	8.0M (1.0%)

	Data Source
13-Sep-09 17:54:31	V\$ACTIVE_SESSION_HISTORY
13-Sep-09 17:59:31	V\$ACTIVE_SESSION_HISTORY
5.0 (mins)	
274	
0.91	
0.23	
SESSION_ID = 14	52.2% of total database activity
	13-Sep-09 17:59:31 5.0 (mins) 274 0.91 0.23

Top User Events

Event	Event Class	% Event	Avg Active Sessions
cursor: pin S wait on X	Concurrency	64.10	0.08
CPU + Wait for CPU	CPU	35.90	0.05

Has my SQL statement's performance changed over time?

AWR Individual SQL Report

- AWR Report for a particular SQL Statement -awrsqrpt.sql
- Useful for researching individual SQL statement performance over time
- Example: Single SQL statement, before and after tuning
- CPU Time per execution substantially decreased – tuning was successful.

Plan Statistics

Before tuning

Stat Name	Statement Total	Per Execution	% Snap Total
Elapsed Time (ms)	571,421	2 747 22	41.67
CPU Time (ms)	569,862	2,739.72	41.71
Executions	208		
Buffer Gets	145,778,328	700,857.35	39.82


After tuning

Stat Name	Statement Total	Per Execution	% Snap Total
Elapsed Time (ms)	33,905	69.48	55.37
CPU Time (ms)	33,920	69.51	56.34
Executions	488		
Buffer Gets	848,144	1,738.00	27.52

Migrating AWR Data


- Why migrate AWR data?
 - To offload analysis from production database
 - To preserve data longer than the production default retention period
 - To do multi-database comparative analysis
- Scripts are located in \$ORACLE_HOME/rdbms/admin


Action	SQL Script
Extract data from AWR into a datapump file	awrextr.sql
Load data from datapump file created by awrextr.sql into a database	awrload.sql



Agenda

- Automatic Workload Repository Infrastructure
- Out of the box AWR reports
- Active Reports






Tip: Use Real-Time SQL Monitoring And Active Reports



- Automatically monitors long running SQL
- Enabled out-of-the-box with no performance impact
- Monitors each SQL execution
- Exposes monitoring statistics
 - Global execution level
 - Plan operation level
 - Parallel Execution level
- Can be saved or emailed as an 'Active Report'





Demo

Active Reports





Conclusion

- AWR contains vast amounts of database performance data
- Enterprise Manager displays a comprehensive view and analysis of that data
- Standard reports can provide additional insights
 - Use the right report for the right problem
- Active reports are a useful new tool for the Oracle database professional



Oracle Helps You Maximize Customer Value



Deploys SOA infrastructure 92% faster



Saves 80% time and effort for managing **Databases**



Avoids online revenue losses up to 25%



Improves IT productivity by 25%



Drives asset utilization up by 70%



Cuts configuration management effort by 90%



Saves \$1.9 million with Oracle Enterprise Manager



Saves \$170,000 per vear with Oracle **Enterprise Manager**



Replaces manual tools with automation: saves time by 50%



Reduces Database testing time by 90%



Reduces provisioning effort by 75%



Saves weeks on application testing time



Cuts application testing from weeks to hours



Reduces critical patching time by 80%



Delivers 24/7 uptime Evanston with Oracle Enterprise Manager

Additional Oracle Enterprise Manager sessions

Wednesday, Oct. 14	Location
 11:45 a.m Performance-Testing Oracle E-Business Suite: Tips and Tricks from Oracle Experts 11:45 a.m Oracle Enterprise Manager: Monitoring and Security Best Practices 11:45 a.m Upgrade Case Study: Database Replay, Snapshot Standby, and Plan Baselines 	 Moscone S. Room 305 Moscone S. Room 303 Moscone S. Room 301
 1:45 p.m Quick Tips for Database Performance Tuning 5:00 p.m SQL Gone Wild: Taming Bad SQL the Easy Way (or the Hard Way) 5:00pm Oracle Enterprise Manager: Beyond the Basics: Getting More from Oracle Enterprise Manager 	 Moscone S. Room 104 Moscone S. Room 102 Moscone S. Room 305

Additional Oracle Enterprise Manager sessions

Thursday, Oct. 15	Location
 10:30 a.m.Everyone Is Applying CPUs (Critical Patch Updates), Right? 10:30 am DBA's New Best Friend: Oracle Database 10g and Oracle Database 11g SQL Performance Analyzer 	 Moscone S. Room 303 Moscone S. Room 102
 12:00 p.m. Worry-Free Application Upgrade Using Oracle Change Management Pack 1:30pm Dell IT's Implementation of Oracle Enterprise Manager Patch Provisioning 	 Moscone S. Room 102 Moscone S. Room 306

ORACLE®